





Oil level Indicators With Thermometer



LS



TS



HOW TO ORDER

LS	3"
SERIES NUMBER	DISTANCE OF CENTER

SPECIFICATION

MODEL	LENGTH mm	WIDTH mm	THICK mm	PITCH mm	THERMO- METER
LS-3"	118	42	18	79	With
LS-5"	182	51	20	127	With
TS-3"	101	36	19	76.2	With
TS-5"	151	36	19	127	With



Gauge Cocks



SB-02



GCT-02L
GCT-03L
GCT-04L



GCT-02
GCT-03
GCT-04

HOW TO ORDER

ST	02	L
SERIES NUMBER	VALVE SIZE	VALVE SIZE L:90°

SPECIFICATION


MODEL		MAX.OPERATED PRESSURE (kgf/cm ²)	RATED FLOW l/min
180°	90°		
ST-02	ST-02L	210	2
ST-03	ST-03L	210	21
ST-04		210	30
GCT-02	GCT-02L	350	2
GCT-03	GCT-03L	350	21
GCT-04	GCT-04L	350	30
SB-02		70	0.5



Glycerine Pressure Gauges



LBD-602P-10



LA-602P-150

HOW TO ORDER

LA	60	2P	150
SERIES NUMBER	DIAL SIZE(mm) 40-1 1/2" 50-2" 60-2 1/2" 75-3" 100-4"	PT(inch) 1P: 1/8 PT 2P: 1/4 PT 3P: 3/8 PT 4P: 1/2 PT	MAX.PRESSURE (kgf/cm ²)

MODEL		DIAL SIZE	PT	PRESSURE RANGE (kgf/cm ²)	
LA	Fill oil, No side, Stand type	40mm	1/8"	1	70
LB	Fill oil, With side, Stand type	1 1/2"	(1P)	2	100
LAD	Fill oil, No side, Insert type	50mm		3.5	150
LBD	Fill oil, With side, Insert type	2"	1/4"	5	200
PA	Reguler, No side, Stand type	60mm	(2P)	7	250
PB	Reguler, With side, Stand type	2 1/2"	3/8"	10	300
PAD	Reguler, No side, Insert type	75mm	(3P)	15	350
PBD	Reguler, With side, Insert type	3"		20	400
		100mm	1/2"	25	500
		4"	(4P)	30	700
				35	1000
				50	