

PRESSURE GAUGES , VACUUM GAUGES , COMPOUND GAUGE WITH ELECTRICAL CONTACT

- SUITABLE FOR AREAS WITH PRESSURE VARIATION.
CAN BE USED AS AN ELECTRICAL CIRCUIT SWITCH
TO AVOID EQUIPMENT BREAKDOWN FROM
HIGH SWITCH FREQUENCY.
- DIAMETER= 4" (100 mm)
- CONNECTION = 3/8", 1/2" PT.
- PRESSURE RANGE = -76cm Hg ~0~
1000kg/cm² (in Hg / psi)
- MATERIAL = CASE & BEZEL: SUS304
WETTED PARTS : SUS316 OR BRASS
- ACCURACY = +/- 1.5%F.S.



BS-HL



DU-H

MICRO PRESSURE GAUGES, VACUUM GAUGES

LOW PRESSURE GAUGES ARE THE IDEAL CHOICE WHEN MEASURING VERY LOW PRESSURE
AND VACUUM GASEOUS MEDIA.

- SUITABLE FOR TOWN GAS INDUSTRY, MEDICAL APPARATUSES & EQUIPMENT ETC .
FOR MEASURING 100MM WATER INJECTION TO 10 PSI POSITIVE & NEGATIVE PRESSURE.
- DIAMETER = 2.5", 3", 4"; 3" IS OF ECCENTRIC THREAD WITH FLANGE.
- PRESSURE RANGE: -500/0 mmAQ (mm H₂O) ~ 0/5000 mmAQ (mm H₂O)
- OPERATING TEMPERATURE: WORKING TEMPERATURE 60°C ; AMBIENT TEMPERATURE
-20 ~ 60°C
- ACCURACY = 1.5 %F.S.



Q-A



Q-AD